

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT-" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator GULF OIL CORPORATION	8. Farm or Lease Name J. N. Carson (NCT-B)
3. Address of Operator P.O. Box 670, Hobbs, NM 88240	9. Well No. 3
4. Location of Well UNIT LETTER <u>B</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>33</u> TOWNSHIP <u>21S</u> RANGE <u>37E</u> NMPM.	10. Field and Pool, or Wildcat Penrose Skelly
15. Elevation (Show whether DF, RT, GR, etc.) 3451' GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

PBTD 3485'. Circulate hole w/abandonment mud. Spot cement plugs from 2600' to 2300' and from 1300' to 1000' w/ Class "C" + 2% CaCl₂. Check csg above 300' at 10' stages until csg will pressure test. Set cmt rtnr @ point csg pres tstd & circ annulus w/Class "C" cmt + 2% CaCl₂. When returns reach annulus surf, squeeze 100 sx cmt below rtnr. Spot 100' surf plug. Install dry hole marker. Clean & clear location.

THE COMMISSION APPROVES AND GRANTS 24 HOURS CLOSURE TO THE CLOSING OF PLUGGING OPERATIONS FOR THE 14103 TO BE APPROVED.

I, I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED N. B. Liles, Jr. TITLE Area Engineer DATE 7-13-79

APPROVED BY Orig. Signed by Jerry Sexton TITLE DATE JUL 17 1979

CONDITIONS OF APPROVAL, Dist. 1: Supv. Expires 1/17/80