Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

	Indicate nature				
REPORT ON BEGINNING DR	ILLING OPERATIONS		REPORT ON	REPAIRING WELL	
REPORT ON RESULT OF SHO TREATMENT OF WELL	OTING OR CHEMICAL		REPORT ON ALTERING	PULLING OR OTHERWI	SE
REPORT ON RESULT OF TE	ST OF CASING	x	REPORT ON I	DEEPENING WELL	
REPORT ON RESULT OF PLU	GGING OF WELL		,		
	Monument, New	Mexi	G O		11, 1937
OIL CONSERVATION COMM Santa Fe, New Mexico.	MISSION,		Place	Date	
Gentlemen:					
Following is a report on the	work done and the res	ults obt	ained under the he	ading noted above at th	e
merada Petroleum Co				Well No. 1	in the
Company or C	of Sec. 33		Lease T	, R 37	, N. M. P. M.,
	Field.	·		-	
The dates of this work were	,				County.
Notice of intention to do the	e work was [submitt	ed on Form C-102	on October 8.	. 1937 19
.0-3/4* 32-3/4# 8-The y the Halliburton Me	ethod wath 300 sa	asing cks.	was set in th	ais w a ll at 323°	and cemented
0-3/4" 32-3/4# 8-Tho by the Halliburton Me the casing was allowed but of the casing and	d. New Lapweld cethod wath 300 saed to stand undisdiff the hole was bar was then run toer had accumulate	easing cks. turbed iled o botto d so	tas set in the driver and allower om again to detect the drilling vertates Drilling	is wall at 323' The cement was to stand undistermine if any was then resumed.	and cemented as then drilled sturbed for vater had
o-3/4* 32-3/4# 8-The by the Halliburton Me the casing was allowed but of the casing and one hour. The bailer scumulated. No water	d. New Lapweld cethod wath 300 saed to stand undisdiff the hole was bar was then run toer had accumulate	easing cks. turbed iled o botto d so	was set in the differ 46 hours dry and allower om again to de the drilling w	is wall at 323' The cement was to stand undistermine if any was then resumed.	and cemented as then drilled sturbed for vater had
o-3/4* 32-3/4# 8-The by the Halliburton Me the casing was allowed but of the casing and one hour. The bailer scumulated. No water	d. New Lapweld cethod with 300 said to stand undisdiffer the hole was bar was then run to er had accumulate	turbed iled d botto	d for 48 hours dry and allower om again to de the drilling v States Drilling Company I hereby swear or is true and correct Name Position Representing American	tis wall at 323' The cement was do stand undistermine if any was then resumed. To affirm that the inform	and cemented as then drilled sturbed for vater had pol-pusher & Par
on 3/4" 32-3/4# 8-The by the Halliburton Me the casing was allowed but of the casing and one hour. The bailer scumulated. No water witnessed by Bill Hand Subscribed and sworn to be allowed by the subscribed by the su	d. New Lapweld cethod with 300 said to stand undisdiffer the hole was bar was then run to er had accumulate BE Name Defore me this Name	turbed iled d botto	d for 48 hours dry and allower om again to de the drilling v States Drilling Company I hereby swear or is true and correct Name Position Representing American	The cement was do to stand undistermine if any was then resumed. To affirm that the information of the company	and cemented as then drilled sturbed for vater had col-pusher & Par Title

Title