


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



DUPLICATE MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Monument, New Mexico,
PlaceJuly 4, 1946
DateOIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation J. G. Hare Well No. 2 in the
Company or Operator Lease

NW 1/4 of SW 1/4 of Sec. 33, T. 21S, R. 37E, N. M. P. M.,
Penrose-Skelley Field, Lea County.

The dates of this work were as follows: July 3, 1946

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on June 29, 1946
and approval of the proposed plan was (~~received~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

6623' TD Lime, Drilled out Depth 6606', Tested Casing with 1000# for 30 Mins was OK, found top of cement at 6575' inside of 5" OD Casing and drilled cement out to 6606' and tested with 1000# for 30 mins was OK. Will Gun perforate from 6490 to 6494' with 16 shots and take drill stem test to find out if cement is OK behind 5" Casing, If cement is OK, will gun perforate from 6494 to 6504, 6516 to 6554 and 6566 to 6602 with 4 shots per foot and complete well.

Witnessed by Don Topper, Amerada Pet. Corp., Asst. Dist. Supt.
Name Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

4 day of July, 1946

Name Don TopperPosition Asst. Dist. Supt.Representing Amerada Pet. Corp.
Company or Operator

My commission expires

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Date JUL 8 1946

Roy Yashinsky
Name
Oil & Gas Inspector
Title