

COUNTY	LEA	FIELD	Blinebry	STATE	NM	OWWO
OPR	AMERADA PETROLEUM CORPORATION					MAP
4 Hare, J. G.						
Sec. 33, T-21-S, R-37-E						
660' fr S Line & 1880' fr W Line of Sec.						
Re-Spud 1-28-65						
Re-Comp 2-17-65						
		CLASS		EL		
		FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING						
13 3/8"	230'	200				
8 5/8"	2735'	1000				
5 1/2"	7938'	500				
LOGS		EL	GR	RA	IND	HC A
		TD 7938', PBD 7335'				

IP Blinebry Perfs 5496-5925' Flwd 142 BOPD. Pot. Based on 20 hr test of 118 BO thru 14/64" chk., IP 1000#, gravity 37.5, GOR 3761.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	TYPE
DATE		

3-1-65 F.R.C. 3-4-65; OWWO, OTD 7938'
Orig. comp from McKee Perfs 7375-7420'
TD 7938', PBD 7335', COMPLETED.
Set CIBP @ 7340', PB to 7335' to shut off
perfs 7375-7420'
Perf 5 1/2" casing @ 5495' W/3 jet shots
Squeezed perf @ 5495' W/325 sx.
Drld out cement
Perf (Blinebry) @ 5496', 5506', 5518',
5536', 5560', 5570', 5582', 5590', 5645',
5660', 5686', 5715', 5726', 5805', 5815',
5823', 5858', 5868', 5875', 5892', 5908',
5916', 5925' W/1 SPI
Ac. 1000 gals
Frac 24,600 gals oil + 31,600# sd. 5496-5925'.