

E	C	B	A	
F	F	G	H	
L	K	J	I	
M	N	O	P	

Designate UNIT well is located in
"E"

DATE STARTED March 24, 1947
DATE COMPLETED May 17, 1947
ELEVATION 3456' Derrick Floor, 3445' Ground
TOTAL FATH S.L. 7856' Drilled out depth 7848'
CABLE TOOLS _____ ROTARY TOOLS X

CASTING RECORD

SIZE	13 3/8"	DEPTH	216'	SAX CEMENT	200
SIZE	8 5/8"	DEPTH	1200 2748'	SAX CEMENT	1200
SIZE	5 1/2"	DEPTH	7856'	SAX CEMENT	600

TUNING RECORD

SITE 2nd EUE

DEPTH 7844' with 1-3' Perforated
Nipple on bottom bull plugged

ACID RECORD

NO. GALS. 500 Gals 1. Acid
 NO. GALS. _____
 NO. GALS. _____

SHOT RECORD

NO. CTS. _____
NO. CTS. _____
NO. CTS. _____

FORMATION TOP-3

Zone 1 (Yates)
Top Eunice Lime
Top Monument Lime

Anhydrite	1170'	Base San Andres	5085'
Top Salt	1260'	Top of Tubbs	6030'
Base Salt	2410'	Base Permian	7355'
Bedrock	2590'	Top Simpson	7375'
Base Lias	2670'	Top Ellenberger	7664'
Bedrock	2710'	Top Granite	7844'
Oil or Gas Pay	7805-7844' (Perforations)		
Water	None		

Initial Production Test No Test Pumping Flowing
Test After Acid or Shot Flowed 590.64 bbls oil on 1" Positive Choke 20 hours

Initial GAS VOLUME 63LM Gas-Oil-Ratio 899

DATE: May 20, 1947

SHIP NAME: Shell Pipe Line Co.

REMARKS: Drilled out depth 7848' COMPANY: Amerada Pet. Corp.,
Perforated 7805-7844 136 holes.
2" Tubing set at 7844' and acidized HIG ID BY: *[Signature]*
with 500 gallons of Western Mud Acid.