

COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name J. G. Hare
3. Address of Operator Drawer D, Monument, New Mexico 88265	9. Well No. 6
4. Location of Well UNIT LETTER <u>L</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>760</u> FEET FROM THE <u>West</u> LINE, SECTION <u>33</u> TOWNSHIP <u>21-S</u> RANGE <u>37-E</u> N14PM.	10. Field and Pool, or Wildcat Paddock
15. Elevation (Show whether DF, RT, GR, etc.) 3462' DF	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plan to run GR Neutron log w/collar locator fr. 5950' to surface. Set bridge plug at 5350'. Spot sand over 5-1/2" csg. perf. fr. 5263' to 5298' & at least to 5258'. Squeeze 5-1/2" csg. perf. fr. 5164' to 5171', 5181' to 5193', 5213' to 5230' & fr. 5233' to 5242' w/150 sks. Class C cement. WOC & drill out cement & wash sand fr. top of bridge plug. Set bridge plug at 5305' & pkr. at 5250' & swab test 5-1/2" csg. perf. fr. 5263' to 5267' & fr. 5278' to 5298'. Re-set bridge plug at 5250' & selectively perforate 5-1/2" csg. opposite Paddock zone subject to logs. Set pkr. at 5200' & swab test. Acidize w/1100 gal. 20% NE acid using ball sealers. Swab back load. Re-set bridge plug at 5200' & pkr. at 5150' & swab test. Acidize w/2400 gal. 20% NE acid using ball sealers. Re-run prod. equipment & resume production.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>E. A. Jones</u>	TITLE <u>Supv. Adm. Ser.</u>	DATE <u>9-6-77</u>
APPROVED BY <u>Jerry Sexton</u>	TITLE <u>Dist. L. Supv.</u>	DATE <u></u>
CONDITIONS OF APPROVAL, IF ANY:		

1200

SEP 8 1977

OIL CONSERVATION COMM.
HOBBS, N. M.