

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
OCT 9 1947
RECEIVED
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL REPORT ON RESULT OF TEST OF CASING SHUT-OFF REPORT ON RESULT OF PLUGGING OF WELL	REPORT ON REPAIRING WELL REPORT ON PULLING OR OTHERWISE ALTERING CASING REPORT ON DEEPENING WELL Report on Plugging Back Well
--	--

October 4, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation

J. G. Hare

Well No. 7

in the _____

Company or Operator

Lease

SW¹ SW¹ of Sec. 33, T. 21S, R. 37E, N. M. P. M.,

Brunson Field, Lea County.

The dates of this work were as follows:

October 3 to 4, 1947

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on October 3, 19 47

and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

8231' Total Depth, Lime & Chert, 8167' PED. Set Baker Model K Cement Retainer at 8170', 8:30PM, 10-3-47. Broke formation at 1800# with 3 bbls. water and squeezed 25 sx. El Toro Cement at 4000#. Pulled up to 8140' and reversed out $\frac{1}{2}$ bbl. cement. Drilled out cement from 8140' to 8167' and perforated with Land Wells from 8150' to 8166', 64 holes. Ran 263 joints of 2" EUE, 4.7#, J-55, R-2, 8-RT, 3" Tubing New and swung at 8163' with 1-3' perforated nipple on bottom and 1-4', 1-1' sub on top. Displaced water with 180 barrels of oil.

Witnessed by K. V. Stephenson Amerada Petroleum Corporation Foreman
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

4th. day of October, 19 47

Name *[Signature]*

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation
Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED
OCT 9 1947
Date _____

[Signature]
Name
Oil & Gas Inspector
Title