

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL	Install flow valves and connect outside gas from Eunice Gas System XX

Hobbs, New Mexico

Place

October 30, 1944

Date

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Gulf Oil Corporation - GYPROD J. N. Carson "C" Well No. 1 in the  
Company or Operator Lease  
C - NE NE of Sec. 33, T. 21, R. 37, N. M. P. M.,  
Hardy Field, Lea County.

The dates of this work were as follows: \_\_\_\_\_

Notice of intention to do the work was (was not) submitted on Form C-102 on \_\_\_\_\_ 19\_\_\_\_  
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Reran tubing at 3743', regular 6' perforated anchor on bottom, 3" collecting chamber 3737'-3645'7", standing valve 3736', 202'5" of 1" tubing 3532' 3734'5", 1" perforated coupling 3553', 2" RUE 10-Thd. x 6" OD casing Lam-Wells ring type hook wall packer at 3546', 375# "K" valve at 3531', 425# "K" valve at 2904'.

Production before: Well averaged 7 bbls. per day and would die frequently.

Production after: Flowed 13 bbls oil and 1 bbl. water last 24 hours.

Witnessed by \_\_\_\_\_  
Name Company Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

30th day of October, 1944

Name J. W. GormanPosition District SuperintendentRepresenting Gulf Oil Corporation - GYPROD  
Company or Operator

Notary Public

My commission expires February 25, 1946Address P. O. Box 1667, Hobbs, New Mexico

Remarks:

Roy Yarbrough  
Name  
Title