


DUPLICATE

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	9-5/8"	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Jan. 27, 1947

Date

Hobbs, N.M.

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Gulf Oil Corporation Carson "C" Well No. 2 in the \_\_\_\_\_  
Company or Operator Lease

NE NE of Sec. 33, T. 21 S, R. 37 E, N. M. P. M.,  
Driskard Field, Lea County.

The dates of this work were as follows: Cemented Jan. 23; tested Jan. 25, 1947

Notice of intention to do the work was (~~7/1/47~~) submitted on Form C-102 on Jan. 24 19 47  
and approval of the proposed plan was (~~7/1/47~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

The hole was washed down and the casing tested with 1200# pressure applied for 30 minutes. The plug was drilled and the hole tested with 1200# pressure applied for 30 minutes. Both tests were OK, and after approval of Mr. Yarbrough, State Oil and Gas Inspector, preparations were made to drill ahead.

Temperature survey showed top of cement behind 9-5/8" casing at 1270' from surface.

Witnessed by H. L. Campbell Gulf Oil Corporation Rotary Foreman  
Name Company Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

27th day of January, 19 47

Name E. J. Gallagher

Position District Sup't.

Representing Gulf Oil Corporation  
Company or Operator

Address Hobbs, N.M.

My commission expires 10-24-49

Notary Public

Remarks:

Roy Yarbrough  
Name  
Oil & Gas Inspector  
Title

FEB 4 1947