

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
17-1/2"	13-3/8"	2921'	300	HOWCO		
13-1/4"	9-5/8"	2960'	1300	"		
8-3/4"	7"	7490'	800	"		

PLUGS AND ADAPTERS

Heaving plug—Material..... Length..... Depth Set.....
 Adapters — Material..... Size.....

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		None				

Results of shooting or chemical treatment.....

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from..... feet to..... feet, and from..... feet to..... feet
 Cable tools were used from..... feet to..... feet, and from..... feet to..... feet

PRODUCTION

Put to producing..... June 20, 1948
 The production of the first 24 hours was..... 417 barrels of fluid of which..... 100% was oil;% emulsion;% water; and.....% sediment. Gravity, Be..... 42.7 API
 If gas well, cu. ft. per 24 hours..... Gallons gasoline per 1,000 cu. ft. of gas.....
 Rock pressure, lbs. per sq. in.....

EMPLOYEES

~~Two States Drilling Company~~..... Driller....., Driller.....
 Driller....., Driller.....

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this..... 8th.....

day of..... July....., 1948

[Signature]
 Notary Public

My Commission expires..... 10-24-49

Place..... Hobbs, New Mexico..... Date..... July 8, 1948
 Name..... Chas Taylor
 Position..... Assistant District Sup't.
 Representing..... Gulf Oil Corporation
 Address..... Box 1667, Hobbs, New Mexico