

# DAILY DRILLING REPORT

E. O. CARSON #8

E. O. CARSON #8, Drinkard Field, Lea County, New Mexico. OBJECTIVE: Prepare well bore for completion as a Drinkard oil well in Central Drinkard Unit operated by Gulf Oil Co. Well to be the CDU #142. AFE #2943 - MOBIL INT. 100% - EST. COST \$7,500.

10/31/72 6615 TD

MIRU DA&S Well Ser Unit, kill well w/ 140 bbls 10# SW, remove tree, instl BOP, POH w/ 107 jts 2-3/8 tbg, pumped in additional 140 bbls SW while pulling tbg, SD for nite.

11/1 E. O. CARSON #8, 6615 TD.  
SI 12 hrs, TP 1100, CP 700, kill well w/ 10# SW, P & LD 94 jts 2-3/8 tbg, SS Baker Model D sealassembly + 5 jts 1" tbg, ran Howco 5" SVDC ret on 2-3/8 tbg set @ 5984, Howco sqzd Tubbs perfs 6125-6339 w/ 150x Class H cmt containing .03% CFR-2 + 3# salt/x, TP 2000, POH w/ tbg & setting tool, SD for nite.

11/2 E. O. CARSON #8, 6615 TD.  
Ran RTTS pkr on 2-3/8 tbg set @ 5304, Howco sqzd Blinbry perfs 5494-5591 w/ 150x Class H cmt containing .03% CFR-2 + 3# salt/x, TP 2600, WOC 2½ hrs, rel pkr, POH w/ tbg & pkr, RU rev unit, SD for nite.

11/3 E. O. CARSON #8, 6615 TD.  
Ran 4½ bit on 4 - 3" DC's & 2-3/8 tbg to 5394, drill cmt to 5519, no cmt to 5591, circ hole clean, test csg to 800#, leaked off to 520#/1 min, POH w/ tbg, DC's & bit, ran RTTS pkr on 2-3/8 tbg to 5304, SD for nite, prep to resqz.

11/4 E. O. CARSON #8, 6615 TD.  
Set RTTS pkr @ 5304, Howco sqzd Blinbry perfs 5494-5591 w/ 150x Class H cmt containing .03% CFR-2 + 3# salt/x, TP 2300, WOC 3 hrs, POH, ran 4½ bit on 4 - 3" DC's and 2-3/8 tbg 3100, SD for nite.

11/6 Finish running bit to 5400, drld cmt to 5592, circ hole clean, test csg to 1000#/ok, drld cmt ret @ 5984 & cmt to 6050, SD for nite & Sunday.

11/7 E. O. CARSON #8, 6615 TD.  
Drill cmt 6050-6101 & Baker Model D pkr 6101-6104, SD for nite.

11/8 E. O. CARSON #8, 6615 TD  
Drilled cmt from 6104-6395, circ clean, test csg 1000# ok then drilled cmt to 6458, SD for nite.

11/9 E. O. CARSON #8, 6615 TD.  
Drill cmt from 6458-6493, test csg 1000#/ok, drill cmt 6493-6500, drill BP 6500-6502 & cmt to 6596, SD for nite.

11/10/72 E. O. CARSON #8, 6615 TD.  
Drill cmt from 6596-6607, ran bit to 6614, circ clean, test csg 1000#/ok, POH w/ tbg, DC's & bit, rerun bit w/ 5" csg scraper to 6614, P & LD tbg, DC's & bit, RD, Rel unit & Rel well to Drinkard Unit @ 4:00 p.m. 11/9/72.  
FINAL REPORT.