

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-101  
Effective 1-1-65

## SUNDRY NOTICES AND REPORTS ON WELLS DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO CLEAN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - C-101 FOR SUCH PROPOSALS.

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER-

2. Name of Operator  
Gulf Oil Corporation

3. Address of Operator  
Box 670, Hobbs, New Mexico 88240

4. Location of Well  
UNIT LETTER 0 660 FEET FROM THE South LINE AND 1980 FEET FROM  
THE East LINE, SECTION 34 TOWNSHIP 21-S RANGE 37-E N.M.P.M.

5a. Indicate Type of Lease  
State ☐ Fee ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name

8. Farm or Lease Name  
Mark Owen

9. Well No.  
2

10. Field and Pool, or Wildcat  
Penrose Skelly

12. County  
Lea

15. Elevation (Show whether DF, RT, GR, etc.)  
3427' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>
		Plugged and abandoned	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3740' TD.

Pulled producing equipment. Set CI BP at 3500' and capped with 79' cement plug, abandoning open hole interval 3575' to 3740'. Found holes in 6" casing at 620' and 844'. Pumped in with fresh water at 1/2 BPM at 750#. Set cement retainer at 715' and pumped 90 sacks of cement thru hole at 844' and circulated cement out of hole at 620'. Dumped 215' cement on top of retainer at 715'. Loaded hole with abandonment mud. Spotted cement plug from 60' to surface. Installed dry hole marker and cleaned location. Plugged and abandoned October 1, 1976.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED D. F. Berlin TITLE Area Engineer DATE October 1, 1976

APPROVED BY / TITLE  DATE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

APR 1 1976  
CC CONSERVATION COMM.  
HOBBBS, N. M.