

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) Clean Out & Free	X	NOTICE OF INTENTION (OTHER) Repr. Csg. Leak	X

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

June 6, 1955
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Mark Owen

Gulf Oil Corporation
(Company or Operator)

Well No. **2** in **0**
(Unit)

SW $\frac{1}{4}$ **SE** $\frac{1}{4}$ of Sec. **34**, T. **21-S**, R. **37-E**, NMPM, **Penrose Skelly** Pool

La County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Propose to clean out to total depth with sand pump if warranted. Treat open hole formation from 3575-3740' with 8000 gallons galled lease crude with Adomite and 1/4 sand per gallon. Run tubing and flow valves.

If production warrants, will repair casing leak as follows:

- 1. Set magnesium bridge plug in base of oil string with 1 sack cement on top.**
- 2. Run HRC tool and locate leak.**
- 3. If leak is above 535' propose to cement thru casing leak by plug method. Will attempt to circulate cement out 6 - 9-5/8" annulus (leak has been established between depths of 525-528').**
- 4. WOC 72 hours. Drill out cement and clean out to bridge plug. Pressure test casing. If OK we will drill out bridge plug and return well to production.**

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

Gulf Oil Corporation
Company or Operator

By **E. F. Taylor**

Position **Area Supt. of Prod.**
Send Communications regarding well to:

Name **Gulf Oil Corporation**

Address **Box 2167, Hobbs, N. M.**