

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) To Fracture	X	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO**Hobbs, New Mexico**
(Place)**February 22, 1956**
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the **F. F. Hardison 2**
Humble Oil & Refining Company Well No. **1** in **H**
 (Company or Operator) (Unit)
SE 1/4 NE 1/4 of Sec. 24, T. 28-S, R. 37-E, NMPM, Hobbs Pool
 (40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)To workover **F. F. Hardison 2-1** as follows:

1. Move in a well and kill well and pull tubing.
2. Run a retrievable bridge plug, 2-1/2 inch tubing and packer which is to be placed in the blank between upper three sets of perforations.
3. Test for communication around blank and if no communication exists, fracture lower two perforated sections with 20,000 gallons refined oil and 20,000 pounds of sand (4070-6135 and 6135-6215). The bridge plug will then be moved to the blank, and the packer set above all perforations and the upper three sets of perforations (5900-5945, 5945-5995, and 6005-6050) fractured. However, if communication does exist, the bridge plug will be left below all perforations and the packer set above all perforations and the entire perforated section (5900-6215) fractured with 20,000 gallons of refined oil and 20,000 pounds of sand. When the well is cleaned up sufficiently through the tubing, the Tubo guns will be placed back on annulus production and the Franchard guns will be reopened for production through the tubing.

Approved **1956**, 19
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy **[Signature]**
Title **Engineer District 1****Humble Oil & Refining Company**
Company or OperatorBy **[Signature]**Position **Agent**

Send Communications regarding well to:

Name **H. H. Rogers**Address **Box 2342, Hobbs, New Mexico**

473