

Humble Oil & Refining Company, Box 2347, Hobbs, N.M.

Form C-103 Continued, Humble Oil & Refining Company, F.F. Hardison B, Well #2, Unit A, Sec 34, T-21-S, Lea County, New Mexico.

10. Set retrievable bridge plug at 6135 and acidized perforations from 6090-6125' w/500 gal NE acid. Test unsatisfactory.
11. Pulled retrievable bridge plug, acidized perforations from 6090-6125 and 6145-6190' w/10,000 gal Jelled NE acid. Test unsatisfactory, would be unable to buck gas line pressure.
12. Set cement retainer at 5975' on wire line.
13. Squeeze cemented Tubbs perforations 6090-6125 and 6145-6190' w/75 sx low fluid loss cement.
14. Re-perforated Blinebry 5902-5914', acidized Blinebry perforations from 5902-5914 w/1000 gal NE acid. Test unsatisfactory.
15. Acidized perforations 5902-5914 w/10,000 gal NE acid. Test unsatisfactory.
16. Set Cast Iron Bridge Plug at 5890' w/2 sx cement on top. Top of cement 5874'.
17. Perforated Blinebry 5801-5815' w/2 jets per ft.
18. Acidized perforations 5801-5815' w/5000 gal. Test unsatisfactory.
19. Sand-oil fraced perforations 5801-5815' w/20,000 gal 2# sand per gallon.
20. Swabbed well in.

1. The first of the two main groups of the

second group, which is the group of the

third group, which is the group of the

fourth group, which is the group of the

fifth group, which is the group of the

sixth group, which is the group of the

seventh group, which is the group of the

eighth group, which is the group of the

ninth group, which is the group of the

tenth group, which is the group of the

eleventh group, which is the group of the