

DISTRICT I
1625 N. French Dr., Hobbs, NM 88240
DISTRICT II
811 South First, Artesia NM 88210
DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410
DISTRICT IV
2040 South Pacheco, Sante Fe, NM 87505

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-025-07010

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.
FEE

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS)

7. Lease Name or Unit Agreement Name
FF Hardison B

1. Type of Well:
Oil Well ☒ Gas Well ☐ Other ☐

8. Well No.
3

2. Name of Operator
Exxon Mobil Corporation

3. Address of Operator **P.O. Box 4358**
Houston TX 77210-4358

9. Pool name or Wildcat
Blinebry Oil and Gas (Oil)

4. Well Location
Unit Letter **G** : **2015** Feet From The **NORTH** Line and **1978** Feet From The **EAST** Line
Section **34** Township **21S** Range **37E** NMPH **Lea** County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3429' DF

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG & ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. (For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion)

2/7/00 - Levelled frac tank area. Killed well. Nipple up blow out preventor.
2/10/00 - Perfed new interval: 5484' - 5626' w/3-1/8"gun, 1 spf.
2/11/00 - Set RTBP @ 5660. Test RTBP to 1000 psi - OK. PU to 5352' and reset pkr. MIRU Petroplex. Pumped 4500 Gals 15% HCL, dropping 150 1.3 SG ball sealers.
2/12/00 - MIRU HES. Frac'd with 174K # 20/40 sand plus 18K # resin coated sand. Total load 1724 bbls.
2/14/00 - TIH and tag sand at 5616'. Bail w/bulldog bailer to 5620'. Bailer plugged. POOH and clean out bailer, remove notched collar on bottom and replace with blade bit. RIH and tag sand at 5620'. Pounded on fill (no success).
2/15/00 - POOH w/bulldog bailer. PU and RIH w/notched collar and hydrostatic bailer. Clean out sand to RBP. POOH with bailer and RBP. Start in hole with production tubing.
2/16/00 - Finishing runnning in hole with tubing and set at 5467'. Nipple down BOP. Flange of well head. RIH with pump and rods.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Linda Koch TITLE **Contract Completion Admin.** DATE **04/04/2001**
TYPE OR PRINT NAME **Linda G. Koch** TELEPHONE NO. **(713) 431-1287**

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE **JUN 03 2002**

CONDITIONS OF APPROVAL IF ANY:

ORIGINAL SIGNED BY
PAUL F. KAUTZ
PETROLEUM ENGINEER

