

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANITARY	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REWORK OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL OR REWORK FOR SUCH PROPOSALS.)		5a. Indicate Type of Lease State ☐ Fee ☒
1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER		5. State Oil & Gas Lease No.
2. Name of Operator Mobil Producing TX. & N.M. Inc.		7. Unit Agreement Name
3. Address of Operator Nine Greenway Plaza, Suite 2700, Houston, Texas 77046		8. Farm or Lease Name Marshall Com
4. Location of Well UNIT LETTER <u>E</u> <u>2230</u> FEET FROM THE <u>North</u> LINE AND <u>330</u> FEET FROM THE <u>West</u> LINE, SECTION <u>2434</u> TOWNSHIP <u>21-S</u> RANGE <u>37-E</u> N.M.P.M.		9. Well No. 6
15. Elevation (Show whether DF, RT, GR, etc.)		10. Field and Pool, or Valued Paddock Pool
12. County Lea		

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
SUBSEQUENT REPORT OF:

NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK ☒ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER ☐	PLUG AND ABANDON ☐ CHANGE PLANS ☐ OTHER ☐	REMEDIAL WORK ☐ COMMENCE DRILLING OPNS. ☐ CASING TEST AND CEMENT JOBS ☐ OTHER ☐	ALTERING CASING ☐ PLUG AND ABANDONMENT ☐
--	---	---	--

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1) MIRU, unseat Baker Double Grip Hydrostatic Packer @ 5079' and pull out of Baker "FA" Packer @ 6320.
- 2) GIH w/4" CIBP and set @ 5500, cap w/7sx cmt
- 3) GIH w/packer and set @ 5000
- 4) Acidize Paddock 5156'-5289' (46 holes) in two stages using 5000 gals of acid - 15% non emulsifying, low surface tension inhibited acid
- 5) Pump acid at 3-5 BPM with a surface treating pressure of 2500#
 - a) Pump 500 gals 5% KCL water w/2 gals/1000 Clay stabilizer
 - b) Pump 2000 gal. acid
 - c) Inject 50 RCNB to obtain selectivity
 - d) Pump 3000 gals. acid
 - e) Flush to perms with 5%, Clay treated KCL water
- 6) Bleed off pressure, unseat packer & POH
- 7) Go back in hole w/tubing anchor, seating nipple and tubing to 5300'
- 8) GIH w/1½" pump on 2600'-7/8" rods and 2700'-3/4" rods
- 9) Hook up and put on pump

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Diane K Black TITLE Authorized Agent DATE 3-10-81

APPROVED BY Jerry Saxon TITLE Dist. In Charge DATE

CONDITIONS OF APPROVAL, IF ANY: