
Santa Fe, New Mexico



in triplicate to the Oil Conservation Commission or its proper agent before as perified ill be returned to the sender on which will be given the approval, with the modifications con-

legulations of the Commission. Indicate nature	of notice by checking below:	
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTEN	TION TO SHOOT OR FREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTEN OTHERWISE A	TION TO PLUG OR LTER CASING
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTEN	TION TO PLUG WELL
NOTICE OF INTENTION TO DEEPEN WELL		
1	lebbs, New Mexico	9 Sept. 1946
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico.		
łentlemen:		Cities Service 011 Course
Collowing is a notice of intention to do certain work	cas described below at the	o 2 in SW SE
of Sec		
Lea County.	The state of the s	
will be tested by bailing the hele dr	Weld Slip Joint Casia conlated. Total depth	g was cemented @ 5305' in of well is 356'. Casing
13-8/8" O.D. 27.3# Armse Spiral Redbed w/ 275 sax of cement which cir will be tested by bailing the hele dr	Weld Slip Joint Casia conlated. Total depth	g was cemented @ 5305' in of well is 356'. Casing
	Weld Slip Joint Casin reulated. Total depth ry after drilling the	g was cemented @ 5305' in of well is 356'. Casing
13-5/8" O.D. 27.35 Armse Spiral Redbed w/ 275 sax of cement which cin will be tested by bailing the hele dr for 1 hr. Approved SEP 13 1945 1945 1945 1945 1945 1945 1945 1945	Weld Slip Joint Casing reulated. Total depth ry after drilling the case of the state of the stat	g was comented © 3365' in of well is 336'. Casing coment plug and let it sto
13-5/8" O.D. 27.35 Armse Spiral Redbed w/ 275 sax of cement which cin will be tested by bailing the hele dr for 1 hr. Approved SEP 13 1945 1945 1945 1945 1945 1945 1945 1945	Weld Slip Joint Casing reulated. Total depth by after drilling the casing the	g was comented © 3365' in of well is 336'. Casing coment plug and let it state of the state of t
13-5/8" O.D. 27.35 Armse Spiral Redbed w/ 275 sax of cement which cir will be tested by bailing the hele dr for 1 hr. ApprovedSEP 13 15 15 15 15 15 15 15 15 15 15 15 15 15	Weld Slip Joint Casing reulated. Total depth by after drilling the casing the	g was comented © 3365' in of well is 336'. Casing sement plug and let it stement plug and let it steme

···

At the first of the second of

A PARTIE OF THE PARTY OF THE PA

ing the second of the second o