Ferm 9-891a (March 1942)				
) i	`*
.5	,			
4 4 4 5 5 4	¥			
<u>, X.</u> ;		٠,		
· · / *				

(SUBMIT IN TRIPLICATE)

Loase No. 005525

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE FLANS	SUBSEQUENT REPORT OF WAYER SHUT-OFF. SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.
	SUBSECUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE.	SUBSPOUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUBSEQUENT REPORT OF ABANDONMENT SUFFIEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL.	
(INDICATE ABOVE BY CHECK MARK F	VATURE OF REPORT, NOTICE, OR OTHER DATA)
	STATE OF THE STATE
	April 22 , 19 50
Wall No Keinath 15 lant 1 1940 fo for	[N] r
with No. As the on . I'm located IDOU it. Iron	$m \begin{bmatrix} N \\ S \end{bmatrix}$ line and 1850 ft. from $\begin{bmatrix} EX \\ W \end{bmatrix}$ line of sec. 8
SE 1 / W 1 21 s	38 e NMPM
LlliottLea	New Mexico
(Field) (County of	r Subdivisien) (State or Tetritory)
The elevation of the derrick floor above sea leve	el is <u>3574</u> ft.
DETAII	LS OF WORK
State names of and expected depths to objective sands; show size: ing points, and all of	s, woights, and lengths of proposed casings; Indicate mudding Jobs, cement her important proposed work)
Feb. 23, 1980- Squeezed perf	orations from 7290 to 7340 with
45 gallons plastic.	
Feb. 23, 1980- Acidiced with	shots per foot from 7120 to 7130. 500 gallons 15% acid.
Well tested approx. 1/8 bbl.	oil per hour before and after
treatment. The oil was sweet	and tested 30 gravity.
Lunderstand that this place of work on the page of work	
	riting by the Geological Survey before operations may be commenced
Company E.M. Elliott	
Address Box 703	
Frankl V	B. C. S. S. See See See See See See See See
Rosuell, N. M.	