FOTU	9-331a
May	y 1939)

(SUBMIT IN TRIPLICATE)

Foloral H. A. Sedmath

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY



## SUNDRY NOTICES AND REPORTS ON WELLS

				I i as a second the	WT DEBODT OF W	ATED CUILT O		
1		ION TO DRILL		1 1	NT REPORT OF W			
			۹S	1	NT REPORT OF SH			
			SHUT-OFF		NT REPORT OF A			1
1			REPAIR WELL		NT REPORT OF R			
			CIDIZE		NT REPORT OF A			
	NOTICE OF INTENT	ION TO PULL OR ALT	ER CASING	SUPPLEME	NTARY WELL HIS	TORY		
ľ	HOUSE OF N	HILE CLOBON WE	drill seter	Teil				
		(INDICATE /	ABOVE BY CHECK MAR	K NATURE OF REP	ORT, NOTICE, OR C	THER DATA)		
				Mala	nd, mane,	Jane 1	7	, 19 44
R	1		2276	<b>AN</b> I	. 1980		<b>K</b> Lili c	8
V	Well No	is locat	<b>2276</b> tedft. f	rom S line	andt	t. from $\{V\}$	$\mathbb{W}$ line of	sec
54	:/4 of NE/4	of 300. 8	<b>T-21-</b> 6	<b>38-</b> S				
	(14 Sec. and	Sec. No.)	(Twp.)	(Range)	(Meri	idian) Maria Mari	ci.eo	
	(Fiel	d)	(Coun	ty or Subdivision)	··· •······		e or Territory)	
			_	3575	Jan Jac	<b>90</b>		
T	The elevation of	of the derrick f	loor above sea l	level is	ft.			
			DET	ATTS OF WO	JBK			
To dr 300'	111. Federal Where S-5/8	-H. A. Kein " easing wil	bjective sands; show ing points, and al ath Sater 6, 11 be set to	11 11. 12 out off o	llengths of propose proposed work) hole to aving hole	be drill • 7-3/	led to a 4" hole	pproximat to be dri
To dr 300' to ap cesia Serfa	rill Federal where 8-5/8 presimately og vill be a nee formatic mied water	-H. A. Keim " easing will " 750'. Sate wet through v a - brown so producing fo	bjective sands; show ing points, and al ath sater 6 11 be set to er bearing fa ater 2020 al and.	be at 725	llengths of propose proposed work) " hole to aving hole t approxim ted.	be dril: - 7-3/4 stsly 7:	Led to a (" hole 25° to 7	pproxima to be dri 50'. 5-1
Po dr 300† 50 ap Bestin Surfa Surfa	Lunderstand th	Hi. A. Keim " easing will 750'. Sate wei through v m - brown so producing for humble 011	bjective sands; show ing points, and al ath Sater 6 11 be set to er bearing for cater some an and.	in writing by the	llengths of propose proposed work) " hole to aving hole t approxim ted.	be dril: - 7-3/4 stsly 7:	Led to a (" hole 25° to 7	pproxima to be dri 50'. 5-1
To dr 309' to ap cesia Surfa Surfa	rill Federal where 8-5/8 presimately og vill be a nee formatic mied water	-H. A. Keim " easing will "50'. Sate of through v a - brown so producing for humble 011	bjective sands; show ing points, and al ath Sater 6 11 be set to er bearing for anter some al and.	sizes, weights, and il other important 11 1. 12 out off or ormation at ad perform be at 725	llengths of propose proposed work) " hole to aving hole t approxim ted.	be dril: - 7-3/4 stsly 7:	Led to a (" hole 25° to 7	pproxima to be dri 50'. 5-1
ro dr 309' to ap sesia Surfa Surfa	rill Federal where 8-5/2 proximately og vill be 1 iee formatic meed water Lunderstand the Company	-H. A. Keim " easing will "50'. Sate of through v a - brown so producing for humble 011	bjective sands; show ing points, and al ath Sater 6 11 be set to er bearing for sater some al and. bractions to nust receive approval & Sefining (	sizes, weights, and il other important 11 1. 12 out off or ormation at ad perform be at 725	llengths of propose proposed work) " hole to aving hole t approxim ted.	be dril: - 7-3/4 stsly 7:	Led to a (" hole 25° to 7	pproxima to be dri 50'. 5-1
To dr 300' to ap cesia Surfa Surfa	rill Federal where 8-5/2 proximately og vill be 1 iee formatic meed water Lunderstand the Company	-H. A. Keim " easing will "50'. Sate of through v a - brown so producing for humble 011	bjective sands; show ing points, and al ath Sater 6 11 be set to er bearing for sater some al and. bractions to nust receive approval & Sefining (	sizes, weights, and il other important 11 1. 12 out off or ormation at ad perform be at 725	llengths of propose proposed work) " hole to aving hole t approxim ted.	be dril: - 7-3/4 stsly 7:	Led to a (" hole 25° to 7	pproxima to be dri 50'. 5-1