

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
NOV 28 1947
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

November 21, 1947

Hobbs, N.M.

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Stanolind Oil & Gas Co. **State C Tract 13** Well No. **5** in the

Company or Operator

Lease

NW/4

of Sec. **36**

T. **21 S**

R. **37E**

N. M. P. M.,

Drinkard

Field,

Lea

County.

The dates of this work were as follows:

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on **11-19** 19 **47**

and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On November 20, 1947 at 4:45 AM, 48 hours had elapsed since running 1410' of 9 5/8" OD casing in subject well and cementing with 700 sacks to be used as intermediate string. At this time casing shut off was tested as follows:

A pressure of 1000# was built up and held for 30 minutes and test being OK cement plug was drilled and a pressure of 1000# again built up and held for 30 minutes. This test, too, being OK, drilling operations were resumed.

Witnessed by **Leslie Martin** **Stanolind Oil & Gas Co.** **Hd. Rsbt.**

Name

Company

Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

25 day of **Nov.**, 19 **47**

Name **Leopold Henderson**

Field Supt.

Position

Representing **Stanolind Oil & Gas Co.**

Company or Operator

Box F; Hobbs, N.M.

Address

My commission expires **6-18-50**

Remarks:

APPROVED **NOV 28 1947**

Date

Roy Yankovich
Name
OIL & GAS INSPECTOR
Title