

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBS OFFICE O. C. C.
NEW MEXICO OIL CONSERVATION COMMISSION
MAY 26 1 03 PM '67

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- T.A.		7. Unit Agreement Name Warren McKee Unit
2. Name of Operator Amerada Petroleum Corporation		8. Farm or Lease Name
3. Address of Operator P. O. Box 668 - Hobbs, New Mexico		9. Well No. 203
4. Location of Well UNIT LETTER K , 1650 FEET FROM THE South LINE AND 2310 FEET FROM THE West LINE, SECTION 7 TOWNSHIP 20-S RANGE 38-E NMPM.		10. Field and Pool, or Wildcat Warren McKee
15. Elevation (Show whether DF, RT, GR, etc.) 3577' DF		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER To Convert to Water Inj. Well <input checked="" type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plan to test csg. for leaks & if necessary repair. Drill out Cal-seal plug at 9174', clean out to TD of 9210' & deepen to approx. 9364'. Run Gamma-Ray Neutron log. Cement 4" liner from 9050' to 9364'. Drill out cement. Perf. first & main sands from approx. 9138' to 9264'. Acidize perfs. with 1500 gals. NE acid. Run 2-7/8" plastic coated tbg. with packer set at 9060'. Place well on injection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED **B. J. Ling** TITLE **District Superintendent** DATE **5-25-67**
 APPROVED BY **John A. Ramsey** TITLE _____ DATE _____
 CONDITIONS OF APPROVAL, IF ANY: