

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

July 13, 1953

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Cities Service Oil Company

Byers

4

F

(Company or Operator)

Well No. in (Unit)

SE 1/4 NW 1/4 of Sec. 7, T. 20S, R. 38E, NMPM, North Warren McKee Pool

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Byers #4 was drilled to a total depth of 9225' in sand. This well was logged by Schlumberger, cored from 9215' to 9225', hydrafraced with 1500 gal Western Fracture Gel, with no show of commercial production.

It is proposed to cut off the 5 1/2" casing at as low a point as it can be found free in the hole and the free csg pulled. The hole will then be loaded with heavy mud and cement plugs spotted as follows: 25 sacks (225') 9000' to 9225', 50 sacks (160') 4512' to 4675', 50 sacks (160') 3940' to 4100' in Greyburg, 50 sacks (160') 3600'-3760' bottom 8 5/8" csg, 3 sacks (10') in top of 8 5/8" csg. No attempt will be made to pull 13 3/8" csg. The cellar and pits will be filled, location leveled and cleaned up and abandoned with a 4" pipe marker cemented in top of the hole and left extending 4' above surface and plugged on top.

Approved **Verbal approval received** 1953, 19____
Except as follows:

Approved
OIL CONSERVATION COMMISSION
By *[Signature]*
Title

Cities Service Oil Company
By *[Signature]*
Position **District Superintendent**
Send Communications regarding well to:
Name **C. M. Hartwell, Cities Service Oil Co.**
Address **Box 97, Hobbs, New Mexico**