

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-07753

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil / Gas Lease No.

7. Lease Name or Unit Agreement Name

Weir, M.E. -B-

8. Well No.

5

9. Pool Name or Wildcat

SWD SAN ANDRES

SUNDRY NOTICES AND REPORTS ON WELL
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☐ GAS WELL ☐ OTHER SWD

2. Name of Operator

TEXACO EXPLORATION & PRODUCTION INC.

3. Address of Operator

205 E. Bender, HOBBS, NM 88240

4. Well Location

Unit Letter M : 660 Feet From The South Line and 766 Feet From The West Line
Section 7 Township 20 Range 38 NMPM Lea COUNTY

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒

ALTERING CASING ☐

COMMENCE DRILLING OPERATION ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-10-97: Move in ; rig up . Install BOP. Release packer & pull out of hole. Ran Bit & Bailer to 2206'. Shut in.

6-11-97: Clean out fill from 4226' to 4237' (PBTD). Pull out of hole. Rig up Rotary Wireline. Ran 300 grain String Shot. Unable to get past 3890'. Pull out of hole. Shut in.

6-12-97: Set pkr. @1793' w/Tailpipe @4103'. Rig up Rotary Wireline. Ran 400 grain, 100' long, primer cord string shot thru tubing. Set off string shot in 6 3/4" Open Hole from 4115' to 4215'. Dowell acidized 6 3/4" Open Hole, 4105'-4237', San Andres Zone, w/3000 gal 15% in 3 equal stages using 500# rock salt blocks between stages. Flush w/38 bbls 2% KCL fresh water. Max pres=1040 psi. Min pres= 497 psi. ISIP=850 psi. On Vacuum in 13 min. Avg rate=2.4 BPM. Shut in.

6-13-97: Release packer & pull out of hole laying down 2 7/8" workstring. Ran tbg & pkr Load annulas w/75 Bbls corrosion inhibited fresh water. Remove BOP. Land Tailpipe @4145' (Bottom of 8 5/8" casing @4105') w/Packer set @2042'. Pressure test annulas to 700 psi for 30 minutes-Held (Chart). Rig down. Open well to disposal at 6 pm.

6-14-97 thru 7-09-97: Testing disposal.

7-10-97: On 24 hour DISPOSAL TEST. Disposed of 452 Bbls produced water at Vacuum tubing pressure. FINAL REPORT.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE J. Denise Leake TITLE Engineering Assistant

DATE 10/1/97

TYPE OR PRINT NAME

J. Denise Leake

Telephone No. 397-0405

(This space for State Use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE ORIGINAL SIGNED BY

GARY W. WINK

OC FIELD REPRESENTATIVE II/STAFF MANAGER

DATE

JUL 30 2002