

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)July 26, 1952
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the SidallTide Water Associated Oil Company

(Company or Operator)

Well No. 1 in 0
(Unit)NE 1/4 NW 1/4 of Sec. 7, T. 20S, R. 38E, NMPM, Wildcat Pool

(40-acre Subdivision)

Lea County.FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

As has been previously reported to the Commission, casing has been set and cemented in this well as follows: 13-3/8" OD. @ 295' with 300 sks. (circulated), 8-5/8" OD. @ 3799' with 1500 sks. (top of cement 1520' from surface) and a 5-1/2" OD liner run from 3651' to 9300' and cemented with 75 sks. (top of cement 8632' from surface). The well has been perforated from 9272-86', tested and has not proved to be productive of oil or gas.

A Halliburton DC retainer was set @ 7360' and a Baker Bridging Plug was set @ 7000'; 8' of cement were put on top of plug. We plan to circulate the hole with 9.5 #/gal mud, shoot off and pull 5-1/2" OD liner from 3651-4300, lay cement plug from 4380-4600, lay a cement plug from 3324-3404, and lay a cement plug in the top of the 13-3/8" surface casing from ground level to 25' below ground level. A 4" OD steel marker extending 4' above the mean ground level will be cemented in the surface casing.

Orig., lcc - OCC lcc - Midland
lcc - Tulsa lcc - Houston
lcc - file

Approved JUL 29 1952, 19
Except as followsTide Water Associated Oil Company
Company or OperatorBy H.P. Shackelford H.P. ShackelfordPosition District Foreman
Send Communications regarding well to:Approved
OIL CONSERVATION COMMISSIONBy [Signature]Name H.P. ShackelfordTitle [Signature]Address Box 547 Hobbs, New Mexico