

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name Warren McKee Unit
3. Address of Operator Drawer D, Monument, New Mexico 88265	9. Well No. 501
4. Location of Well UNIT LETTER <u>0</u> <u>330</u> FEET FROM THE <u>South</u> LINE AND <u>1650</u> FEET FROM THE <u>East</u> LINE, SECTION <u>7</u> TOWNSHIP <u>20S</u> RANGE <u>38E</u> NMPM.	10. Field and Pool, or Wildcat Warren McKee Simpson

15. Elevation (Show whether DF, RT, GR, etc.)

3576' DF

12. County

Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

February 20, 1985 to March 4, 1985 - Pulled rods, & pump. Swabbed water. Pulled tapered string of 2-7/8" & 2-3/8" tbg. & laid down thirteen bad joints of 2-3/8" tbg. Ran 5-1/2" retrievable bridge plug & 5-1/2" pkr. & set bridge plug in 5-1/2" csg. at 8437' & tested w/1000# press. Held OK. Located 5-1/2" csg. leak between 4479' & 4541'. Spotted 2 sks. sand on top of bridge plug at 8437'. Set cement retainer at 4349' & squeezed 5-1/2" csg. leak between 4479' & 4541' w/400 sks. Class C cement with 321 sks. cement in formation, left 19 sks. cement inside 5-1/2" csg. below cement retainer and reversed out 60 sks. cement. WOC & checked top of cement inside 5-1/2" csg. at 4336'. Drld. cement fr. 4336' to 4349' & drld. cement retainer fr. 4349' to 4351' & drld. good cement fr. 4351' to 4541' & cement stringers fr. 4541' to 4571'. Circ. hole clean & pressured up on 5-1/2" csg. to 500#. Held OK. Washed sand fr. retrievable bridge plug at 8437' & recovered bridge plug. Re-ran tbg., pump & rods and resumed pumping.

No test reported.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. B. Fisher

TITLE Supv. Adm. Ser.

DATE 3-8-85

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT 1 SUPERVISOR

TITLE

DATE

MAR 11 1985

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAR 11 1985

O.C.B.
HONORARY OFFICE