

DEPTH INTERVALFORMATION AND PERCENTAGE

6650	6660	Lime 10%, Dolo 90%
6660	6670	Dolo 100%
6670	6700	Dolo 100%, Tr. Blk. Shale
6700	6710	Dolo 90%, Sand 10%
6710	6760	Dolo 100%
6760	6790	Dolo 100%
6790	6870	Dolo 100%, Tr. Blk. Shale
6870	6920	Lime 100% (20-30St)
6920	6930	Lime 100%, Tr. Chert.
		D. S. T. 6858-6884- Open 40 Min. Recovered 20' mud.
		D. S. T. 6850 - 6924- open 80 Min. Recovered 70' slightly gas cut Mud.
6930	6980	Lime 100%
6980	6990	Lime 80%, Dolo 20%
6990	7000	Lime 30%, Dolo 70%, 20% St.
7000	7010	Lime 50%, Dolo 50% 70% St. Tr. Blk. Shale
7010	7020	Lime 10%, Dolo 90% (50% St.)
7020	7030	Lime 20%, Dolo 80%, 30% St.
7030	7040	Lime 20%, Dolo 80%, (P) (30% St.)
7040	7050	Lime 10%, Dolo 90% (P) (90% St.)
7050	7060	Lime 10%, Dolo 90%, (PPP) (90% St.)
7060	7065	Lime 70%, Dolo 30%, (P) (30% St.)
7065	7070	Lime 10%, Dolo 80%, (P) (30St. Sand 10%
		D. S. T. 6940-7065 Open 120 Min. Recovered 300' gas Cat mud,
		1,000' Muddy salt water & 800' Salt Water.
7070	7080	Lime 50%, Dolo 50%, (P) (70% St.)
7080	7090	Lime 100% (50% St.)
7090	7100	Lime 20%, Dolo 80%, (P) (80% St.)
7100	7110	Lime 20%, Dolo 80%, (P) (50% St.)
7110	7120	Lime 50%, Dolo 50% (50% St.)
7120	7180	Lime 100%
7180	7200	Lime 90%, Bent. Shale 10%
7200	7220	Lime 90% Bent. Shale 10%, Tr. Chert
7220	7230	Lime 95% (P) (30% St.) Sand 5%
7230	7240	Lime 95% Blk. Shale 5%
7240	7260	Lime 90%, Bent. Shale 10%
7260	7270	Lime 60%, Dolo 40%
7270	7280	Dolo 100%
7280	7290	Lime 60%, Dolo 40% (20% St.)
7290	7300	Lime 50%, Dolo 50%
7300	7310	Dolo 100% (20% St.)
7310	7320	Dolo 100% (10% St.)
7320	7330	Dolo 100%
7330	7340	Lime 40%, Dolo 60%, (10% St.)
7340	7350	Lime 40%, Dolo 60%
7350	7380	Dolo 100%
7380	7390	Lime 10%, Dolo 80%, Bent. Shale 10%
7390	7400	Dolo 90%, Bent. Shale 10%, Tr. Chert
7400	7410	Dolo 100%
7410	7430	Dolo 100%
7430	7440	Dolo 90%, Bent. Shale 10%
7440	7450	Dolo 100%
7450	7460	Lime 40%, Dolo 60%
7460	7470	Lime 100%
7470	7480	Dolo 100%
7480	7490	Lime 10%, Dolo 90%, Tr. Blk. Shale
7490	7500	Lime 20%, Dolo 70%, Bent. Shale 10%
7500	7520	Lime 100%, Tr. Blk. Shale
7520	7530	Lime 100%
7530	7540	Lime 70%, Dolo 30%
7540	7550	Lime 40%, Dolo 60%, (P)
7550	7560	Dolo 90%, Bent Shale 10%
7560	7570	Lime 10%, Dolo 90%
7580	7580	Dolo 90%, Bent Shale 10%
7590	7600	Dolo 100%
7600	7610	Dolo 100%
7610	7620	Dolo 90%, Bent Shale 10%
7620	7630	Dolo 100%
7630	7640	Dolo 80%, Bent Shale 20%
7640	7650	Lime 10%, Dolo 90%, (P) (10% St.)
7650	7660	Dolo 90%, Bent. Shale 10%
7660	7670	Dolo 100%
7670	7680	Dolo 90%, Bent. Shale 10%
7680	7690	Lime 20%, Dolo 80%
7690	7700	Lime 20%, Dolo 70%, Bent. Shale 10%
7700	7710	Lime 10%, Dolo 90%, (P) (20% St.)

