


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

December 21, 1949

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Stanolind Oil and Gas Company D. E. Howse "A" Well No. 1 in the

Company or Operator _____ Lease _____
SE/4 of Sec. 11, T. 20, R. 38, N. M. P. M.,
House Field, Lea County.

The dates of this work were as follows: December 13-14-15, 1949

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on December 14 19 49
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On December 15, 1949, at 11:00 p.m. 48 hours had elapsed since running 3829' of 8-5/8" casing set at 3841' and cemented with 950 sacks to be used as intermediate string. Cement was circulated and located at 2325' by temperature survey.

Pipe and water shut off was tested by applying 1000 psi pressure and holding for 30 minutes before and after drilling cement plug. No pressure drop occurred on either test. Drilling was resumed.

Elevation 3579 DF.

Witnessed by T. S. Holden Stanolind Oil and Gas Co. Head Ronstabont.
Name Company Title

Subscribed and sworn before me this 21st

I hereby swear or affirm that the information given above is true and correct.

day of December 19 49

Name Robert J. Henderson

Position Field Superintendent

Representing Stanolind Oil and Gas Company

Company or Operator

My commission expires 2-23-50

Address Box F, Hobbs, New Mexico

Remarks:

Notary Public
Name
Title