
Depth & For ATT

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

REPORT ON BEGINN				
REPORT ON BEGINNING DRILLING OPERA-		REPORT ON REPAIRING WELL		
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING		SE
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL		
REPORT ON RESULT (OF PLUGGING OF WELL			
	B	ecember 5, 1949		New Mexico
OIL CONSERVATION O SANTA FE, NEW MEX Gentlemen:		Date	Pla	C6
	the work done and the results of			
	any or Operator	Lease	Well No	in the
	of Sec		_, R <u>38</u>	_, N. M. P. M.,
· · · · · · · · · · · · · · · · · · ·	Field,		-	•
	vere as follows:			
	o the work was (************************************	- · · · · · · · · · · · · · · · · · · ·	• •	19 LQ
On November 26. 1	949. at 2:30 a.m. 36 h		TS OBTAINED	l of
13-3/8" casing se string. Cement w by applying 500 p	1949, at 2:30 a.m. 36 het at 317 and cemented was circulated to surfaces pressure and holding essure drop did not occ	ours had elapsed with 400 sacks to ce. Pipe and wate g for 30 minutes	since running 307 o be used as surfa er shut off was to before and after o	ace ested irilling
13-3/8" casing se string. Cement w by applying 500 p cement plug. Pre	et at 317° and cemented was circulated to surfa- esi pressure and holdin	ours had elapsed with 400 sacks to ce. Pipe and wate g for 30 minutes our on either test	since running 307 to be used as surfa er shut off was to before and after of . Drilling was re	ace ested irilling esumed.
13-3/8" casing se string. Cement w by applying 500 p cement plug. Pre	et at 317° and cemented was circulated to surfa- psi pressure and holdin essure drop did not occ T. S. Holden Name	ours had elapsed with 400 sacks to ce. Pipe and water for 30 minutes our on either test. Stanolind Oil Company	since running 307 to be used as surfacer shut off was to before and after of Drilling was re I & Gas Company I	ested irilling esumed.
13-3/8" casing setting. Cement we by applying 500 p cement plug. Pre	et at 317° and cemented was circulated to surfa- psi pressure and holdin essure drop did not occ T. S. Holden Name	ours had elapsed with 400 sacks to ce. Pipe and water for 30 minutes our on either test. Stanolind Off Company I hereby syear or after the control of the	since running 307 to be used as surfacer shut off was to before and after of Drilling was re I & Gas Company I	ested irilling esumed.
13-3/8" casing setting. Cement we by applying 500 p cement plug. Pre	et at 317' and cemented fas circulated to surfa- posi pressure and holding essure drop did not occ T. S. Holden Name before me this 5th	ours had elapsed with 400 sacks to see. Pipe and water for 30 minutes for 30 minutes for on either test. Stanolind Oi Company I hereby swear or affice true and correct.	since running 307 to be used as surfacer shut off was to before and after of Drilling was re I & Gas Company I	ested irilling esumed.
13-3/8" casing setting. Cement we by applying 500 p cement plug. Pre	et at 317' and cemented fas circulated to surfa- posi pressure and holding essure drop did not occ T. S. Holden Name before me this 5th	stanclind Officery Stancling Stance Officery Stance Office	since running 307 to be used as surfacer shut off was to before and after of the before and after the before the before and after the bellipse and after the before and after the before and after the be	ested irilling esumed. Id. Rabt. Title n given above
13-3/8" casing setting. Cement we by applying 500 p cement plug. Pre	t at 317' and cemented to surfaces circulated to surfaces pressure and holding essure drop did not occur. T. S. Holden Name before me this 5th Notary Public	ours had elapsed with 400 sacks to see. Pipe and water for 30 minutes are on either test. Standlind Oi Company I hereby swear or afficient is true and correct. Name Position Field Representing Stand	since running 307 to be used as surfacer shut off was to before and after of the company of the	ested irilling sumed. Id. Rabt. Title n given above
13-3/8" casing setting. Coment we by applying 500 proment plug. Proment plug. Proment plug. Subscribed and sworn day of the su	t at 317' and cemented to surfaces circulated to surfaces pressure and holding essure drop did not occur. T. S. Holden Name before me this 5th Notary Public	ours had elapsed with 400 sacks to see. Pipe and water for 30 minutes are on either test. Standlind Oi Company I hereby swear or afficient is true and correct. Name Position Field Representing Stand	since running 307 to be used as surfacer shut off was to before and after of the surface of the	ested irilling sumed. Id. Rabt. Title n given above