

**DUPLICATE**

NEW MEXICO OIL CONSERVATION COMMISSION

MISCELLANEOUS REPORTS ON WELLS

**RECEIVED**  
MAY 27 1952  
DISTRICT OFFICE

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<b>X</b>		

May 27, 1952

Monument, New Mexico

Date

Place

Following is a report on the work done and the results obtained under the heading noted above at the

**Amerada Petroleum Corporation** Fred Turner Jr "B" Well No. **1** in the  
 Company or Operator Lease  
**SE/4, NW/4** of Sec. **17**, T. **20-S**, R. **38-E**, N. M. P. M.,  
**North Warren-McKee** Pool **Lea** County.

The dates of this work were as follows: **May 22, 1952**

Notice of intention to do the work was ~~XXXXXX~~ submitted on Form C-102 on **May 22, 1952**, 19\_\_\_\_, and approval of the proposed plan was ~~XXXXXX~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

**8-5/8" casing set @ 3696'**  
**9561' T.U. 3584' PBD./ Well Plugged and abandoned.** Went in hole with open end tubing and spotted 35 Sacks regular cement - pulled tbg. to 8050' and spotted 35 sacks regular cement - pulled tbg. to 4150' and spotted 55 sacs regular cement mixed 4% calcium chloride - pulled tbg to 4047' and spotted 40 sacks regular cement mixed 4% calcium chloride - pulled tbg. to 3696' and spotted 35 sacks regular cement. Checked top of cement at 3584'. Filled hole with heavy drlg mud between each plug. Finished filling hole with heavy drilling mud. Installed 4" Master valve on top of 8-5/8" casing, and piece of 4" line pipe to extend 5' above the ground level, as marker. Well plugged and abandoned @ 4 PM, 5/22/52

Witnessed by **T. M. Mackey** **Amerada Petroleum Corporation** **Farm Boss -**  
 Name Company Title

APPROVED:  
 OIL CONSERVATION COMMISSION

*May Yarrrough*  
 Name  
 Title  
 Date

I hereby swear or affirm that the information given above is true and correct.

Name  
 Position **Assistant District Superintendent**  
 Representing **Amerada Petroleum Corporation**  
 Company or Operator  
 Address **Drawer D, Monument, New Mexico**