

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

SEP 18 1952

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

## Indicate Nature of Report by Checking Below

|   |  |   |                                     |                          |  |
|---|--|---|-------------------------------------|--------------------------|--|
| REPORT ON BEGINNING DRILLING OPERATIONS |  | REPORT ON RESULT OF TEST OF CASING SHUT-OFF | <input checked="" type="checkbox"/> | REPORT ON REPAIRING WELL |  |
| REPORT ON RESULT OF PLUGGING WELL       |  | REPORT ON RECOMPLETION OPERATION            |                                     | REPORT ON (Other)        |  |

September 16, 1952

Monument, New Mexico

(Date)

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation

Mary J. Raley "A"

(Company or Operator)

(Lease)

Creekmore Drilling Company

1

C/NE/4 of NE/4

18

(Contractor)

Well No. in the 1/4 of Sec.

T. 20-S, R. 3-E, NMPM, North Warren-McKee Pool, Lea County.

The Dates of this work were as follows: September 15, 1952

Notice of intention to do the work (was) (~~XXXX~~) submitted on Form C-102 on \_\_\_\_\_, 19\_\_\_\_, (Cross out incorrect words)

and approval of the proposed plan (was) (~~XXXX~~) obtained.

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

9260' Total Depth. 9250' Drilled out Depth - Sand & Shale. Finished drilling 6-3/4" hole at 2:35 PM, 9/12/52. Ran Schlumberger's Electrical, Gamma Ray and Microlog Surveys. Ran 2 1/4 Jts of 5 1/2" casing set at 9260' with 600 sacks cement - Ran temperature survey, top of cement outside 5 1/2" casing at 5645', or, 125% fill. After WOC for 24 hours, tested casing for 1/2 hour with 800# - no pressure drop. Drilled cement from 9170' to 9250' and tested 5 1/2" casing with 800# for 1/2 hour - no pressure drop. Continued with completion operations -

Witnessed by T. M. Mackey Amerada Petroleum Corporation Farm Boss -  
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name Don J. [Signature]Position Assistant District SuperintendentRepresenting Amerada Petroleum CorporationAddress Drewer D, Monument, New Mexico

(Title)

(Date)