

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or _____ per
agent not more than twenty days after completion of well. Follow instructions
in the Rules and Regulations of the Commission. Indicate questionable data
by following it with (?). **SUBMIT IN TRIPLICATE.**

AREA 640 ACRES
LOCATE WELL CORRECTLY

LOCATE WELL CORRELATE

Amerada Petroleum Corporation - Monument, New Mexico **Fred Turner Jr "A"**
Company or Operator Lease

Well No. **5** in **SW/4, NE/4** of Sec. **18**, T. **20-S**

R. **33-E**, N. M. P. M., **Skaggs** Field, **Lea** County.

Well is **1980** feet south of the North line and **1980** feet west of the East line of **Section 18**

If State land the oil and gas lease is No. **-** Assignment No. _____

If patented land the owner is **Fred Turner Jr**, Address _____

If Government land the permittee is _____, Address _____

The Lessee is **Amerada Petroleum Corporation**, Address **P.O. Box 2040, Tulsa, Oklahoma**

Drilling commenced **2/22/52** 19____ Drilling was completed **3/2/52** 19____

Name of drilling contractor **Baker & Taylor Drilling Company**, Address **First Nat'l. Bank Bldg.,
Amarillo, Texas**

Elevation above sea level at top of casing **3553** feet.

The information given is to be kept confidential until **Not Confidential** 19____

OIL SANDS OR ZONES

No. 1, from 3810 to 3916 No. 4, from _____ to _____
 No. 2, from _____ to _____ No. 5, from _____ to _____
 No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet. _____

No. 2, from _____ to _____ feet. _____

No. 3, from _____ to _____ feet. _____

No. 4, from _____ to _____ feet. _____

CASING RECORD

[illegible]

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
13-3/4	8-5/8	272	200	Halliburton		
7-7/8	5-1/2	3710	1000	Halliburton		

PLUGS AND ADAPTERS

Heaving plug--Material _____ Length _____ Depth Set _____
Adapters--Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		DuPont Safety Stick Nitro #1	34.5 Qts	3/9/52	3780-3918	3918'

Results of shooting or chemical treatment **Flowed 137.97 bbl oil, .07 bbl E.S. O-Water in 19 hours on 16/64" choke. TP 175# Gas Vol. 209,780 cu ft p/d. GOR 1204. Qty 37.3 Corrected.**

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0' feet to 3918' T.D. feet, and from _____ feet to _____ feet.

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

PRODUCTION

Put to producing March 12, 1952, 19

The production of the first 24 hours was 174.31 barrels of fluid of which 99.96 % was oil; % emulsion; % water; and .04 % sediment. Gravity, Br 37.3

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

John S. Noland, Driller J. H. Hargis, Driller
E. J. Locke, Driller

FORMATION RECORD ON OTHER SITE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 14th
day of March, 1952
[Signature]
Notary Public
My Commission expires 8/23/55

Monument, New Mexico
Place Date
Name _____
Position Assistant District Superintendent
Representing Amerada Petroleum Corporation
Company or Operator.
Address Drawer D, Monument, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	6	6	Cellar
6	1404	1398	Red Bed, Shale and Sand
1404	1510	106	Anhydrite, Red Sand & Shale.
1510	2525	1015	Salt, Polyhalite and Anhydrite
2525	2650	215	Anhydrite
2650	2790	140	Red Sand and Anhydrite
2790	3480	690	Dolomite and Anhydrite
3480	3918	438	Dolomite, Anhydrite and Sand
	3918		Total Depth -

GEOLOGICAL DATA

Top Anhydrite	1430
Top Salt	1540
Base Salt	2540
Top Yates	2683
Top Monument Line	2833
Elevation	3566 D.F.

SLOPE TESTS

850'	-3/4 Deg.
1340	-3/4
2000	-3/4
2600	1-1/4
3168	3-

DRILL STEM TESTS

N O N E