

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR
CONOCO INC.

3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL + 1830' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
LC-031670 (B)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
NMFU

8. FARM OR LEASE NAME
SEMUA30

9. WELL NO.
71

10. FIELD OR WILDCAT NAME
UNDESIGNATED A30

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 18, T-20S, R-38E

12. COUNTY OR PARISH
LEA

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	☐	☐
FRACTURE TREAT	☐	☐
SHOOT OR ACIDIZE	☐	☒
REPAIR WELL	☐	☐
PULL OR ALTER CASING	☐	☐
MULTIPLE COMPLETE	☐	☐
CHANGE ZONES	☐	☒
ABANDON*	☐	☐
(other)	☐	☐

(NOTE: Report results of multiple completion or change on Form 9-330.)

RECEIVED
NOV 21 1 54 AM '83
BUREAU OF LAND MANAGEMENT
ROSWELL DISTRICT

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU 10/22/83. DO CIBP @ 7520'. SET CIBP @ 7850'. SPOTTED 14 BLS 15% HCL-NE-FE @ 7770'. PERF LOWER A30 w/2 JSPF @ 7488', 7514', 25', 34', 40', 43', 52', 58', 66', 74', 83', 89', 95', 7620', 30', 46', 50', + 7657'. SET PKR @ 7321'. ACIDIZED PERFS w/60 BLS 15% HCL-NE-FE. FLUSHED w/56 BLS 9 PPG BRINE. SWBD. REL PKR. SET RBP @ 7474'. SPOTTED 15 BLS 15% HCL-NE-FE @ 7462'. PERF MIDDLE A30 w/2 JSPF @ 7276', 81', 87', 99', 7309', 24', 36', 41', 51', 59', 64', 71', 80', 87', 94', 7402', 13', 24', 35', 40', 48', 55', + 7462'. SET PKR @ 7127'. ACIDIZED PERFS w/80 BLS 15% HCL-NE-FE. SWBD. REL PKR. RESET RBP @ 7263'. SPOTTED 12 BLS 15% ACID @ 7256'. (ATTACHMENT)

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm A. Butler TITLE Administrative Supervisor DATE 11/18/83

ACCEPTED FOR RECORD

PETER W. CHESTER

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL: 1 1984

RECEIVED

MAR 7 1984

O.C.D.
HOBBS OFFICE

SEMU ABO No. 71

RECOMPLETION

PERF UPPER ABO w/ 2 JSPF @ 7083', 7110', 18', 27', 30', 38', 46', 49', 55', 60', 70', 73', 77', 80', 96', 7200', 04', 08', 13', 19', 23', 30', 35', 40', 45', + 7252'. SET PKR @ 6936'.

ACIDIZED PERFS w/ 90 BBLs 15% HCL-NE-FE. FLUSHED w/ 52 BBLs 9 PPG BRINE. SWBD. REL PKR + RBP. RAN PRODUCTION EQUIPMENT w/ PKR SET @ 7003'. SWBD. FLOWED 363 BO, 8 BW, + 850 MCF IN 24 HRS ON 15/64" CHK + 850 PSI FTP 11/10/83.

(WELL COMPLETION REPORT TO FOLLOW.)