

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPI  
(Other instructions  
reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 031670 (6)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

L ☒ GAS WELL ☐ OTHER

7. UNIT AGREEMENT NAME

CONTINENTAL OIL COMPANY

8. FARM OR LEASE NAME

SEMU McKEE

P.O. Box 460, HOBBS, N.M. 88240

9. WELL NO.

71

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
e also space 17 below.)

surface

10. FIELD AND POOL, OR WILDCAT

WARREN McKEE

660' FSL & 1830' FEL of Sec. 18

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 18, T. 20S, R. 38E

PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3562' DF

12. COUNTY OR PARISH

LEA

13. STATE

N.M.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other)

REPAIR CASING

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

RAN Casing bond log. Perf 3836'-39' w/2 TSPF. 5g. parts w/116 sks. Class "C" cmt. Perf 159 3659'-62' w/2 TSPF. Pmpd 150 sks. Cl. "C" cmt. Unable to hold pres. Flushed perfs. Pmpd 150 sks Class "C" cmt. No squeeze. Cleared perfs & waited 5 hrs. Attempt to stage squeeze 150 sks. Class "C" cmt w/no results. Set retainer @ 3437. Mixed 100 sks. Class "C" cmt, left 35 sks cmt. below retainer w/2300 psi. Drilled out cmt retainer. Drilled out cmt & tested both sets perfs w/1000 psi each. Held ok. Work started 2-16-74, completed 2-24-74.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

SR. ANALYST

DATE

2-18-75

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

US68-5, File

ACCEPTED FOR RECORD

FEB 20 1975

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO