

Form 9-331a
(Feb. 1951)

Land Office Las Cruces

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED

AUG 21 1952

U. S. GEOLOGICAL SURVEY
ON CONSERVATION COMMISSION

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

W. D. Burger B-18 No. 1-S

Hobbs, New Mexico May 27, 1952

Well No. 1-S is located 660 ft. from N line and 1830 ft. from E line of sec. 18

SE 1/4 Section 18 20S 38E N. M. P. 16
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Undesignated Lee New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well at the above location to a total depth of approximately 9300' with rotary tools to obtain commercial production in the Simpson. All casing points will be cemented in accordance with approved methods of the U. S. Geological Survey and any other special requirements will be complied with.

It is planned to use the following casing pattern: 13" casing to be set at 250' and cemented with approximately 250 sacks cement, cement to be circulated; 9 5/8" casing to be set at approximately 2800' and cemented with 1780 sacks cement or sufficient cement to protect the salt section as determined by survey; 7" casing to be set at total depth and cemented with 730 sacks cement or as determined by survey and to be perforated opposite the pay zone.

Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Box 427

Hobbs, New Mexico

By Ch. Miller

Title District Superintendent

1. The first of these is the fact that the
 2. of the system is not a simple one.
 3. The second is the fact that the
 4. of the system is not a simple one.
 5. The third is the fact that the
 6. of the system is not a simple one.

The first of these is the fact that the
 of the system is not a simple one.
 The second is the fact that the
 of the system is not a simple one.
 The third is the fact that the
 of the system is not a simple one.
 The fourth is the fact that the
 of the system is not a simple one.
 The fifth is the fact that the
 of the system is not a simple one.