

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
CONTINENTAL OIL COMPANY
3. ADDRESS OF OPERATOR
Box 460, Hobbs, NM 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL + 1980' FEL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Report Blinbry ☒

- ☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE

L.C. 031670 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

SEM U

8. FARM OR LEASE NAME

Semaburger

9. WELL NO.

21

10. FIELD OR WILDCAT NAME

Skaggs Drkd East (Gas) R-6005

Skaggs Drkd West Blinbry
Skaggs Drkd East Blinbry

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 19, T-20S, R-38E

12. COUNTY OR PARISH

Lea

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3546' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Rig up and unseat pump. Hot oil Tbg. Pull Prod Equip. Tag to 11. CO scale to 6888'. Spot 500 gal 15% HCL NEFE acid across Drkd pnts. Ran Baker Lok-set RBP and set plug at 6130'. Spot 1000 gal 15% HCL NEFE Acid across Blinbry pnts. Perf Blinbry w/ 15SPF at 5831', 541', 70', 5934', 37', 56', 69', 97', 6012', 44', 49', 56', 94', 97', and 6100'. Release RBP. Ran 2 7/8 Tbg open ended w/ SN at 6846'. Ran Prod. Equip. and Release Rig. Tested 2-7-78 for 24 1/2 hrs w/ 12 oil, 25 water, 155 mcf.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Wm. B. Butterfield

TITLE

Admin. Supv.

DATE

5-17-78

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD

MAY 19 1978

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

11 C.C.S.-5 NM FIA P-12400-4. File