

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
CONOCO INC.
3. ADDRESS OF OPERATOR
P.O. Box 460, HOBBS, N.M. 84240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL & 1980' FWL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON* ☐
- (other) ☐

SUBSEQUENT REPORT OF:

- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☒
- ☐

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)
APR 16 1980U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

5. LEASE
LC-031670 B
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
SEMU
8. FARM OR LEASE NAME
SEMU BURGER B
9. WELL NO.
13
10. FIELD OR WILDCAT NAME
WARREN MCKEE
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 20, T-20S, R-38E
12. COUNTY OR PARISH
LEA
13. STATE
N.M.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3554' DF

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU 1-23-80. Squeezed off Drinkard perfs @ 6780', 83' 6818', 30', 37', & 6853' w/ 150 sx. class "C" cement. w/ additives. Drilled out cement from 6525' - 6855' Tested upper Drinkard perfs - held OK. Drilled out cement from 6865' to 6890'. Tested lower Drinkard perfs - held. Tagged Fill @ 6985'. Drilled up CIBP @ 7000'. Ran tapered 7bg. string (1 3/4" & 2 7/8"). Set 7bg. @ 8981'. Well pumped 2 BOPD, 4 BWP, gas TSTM.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm A. Rutherford TITLE Admin. Supervisor DATE 4/17/80

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

4565-5
NMFU-4
FILE