

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 750' TSC + 1650' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

15. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other) STRAIGHTEN 170' C ☒

SUBSEQUENT REPORT OF:

U. S. GEOLOGICAL SURVEY
HOBBS NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1-16-79 hole in subject drilling well WAS STRAIGHTENED AS FOLLOWS:

spot cmt plug from 1400'-150' w/ 900 sk class cmt.

1-17- begin dng 8 3/4" hole

1-18 Drill to 1330' DEV. 0°, begin opening hole to 12 1/4"

1-21 Reached SURF. CSG TO 1355' KB. DEV. 1/2°. Ran CSG as follows:
95/8 GS, SJ, FC, 33 JTS 95/8 36" K-55 ST SC set @ 1355'

cmt w/ 625 sk class cmt + additives; circ 35 sk to surf

WD. C. 18 hrs. press test to 1000 psi for 30 mins held ok.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Wm. A. ButterfieldTITLE Admin. SupvDATE 1-22-79

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

4565 5NMFU 47.10.

*See Instructions on Reverse Side