

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Joseph I. O'Neill, Jr.

209 N. Big Spring

Midland, Texas

Kornegay

Well No. 1

in NW NE

of Sec. 21

T. 20-S

R. 38 E

N. M. P. M.

Wildcat

Field,

Lea

County.

Well is 660

feet south of the North line and

1980

feet west of the East line of

Section 21

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Earl Kornegay Address Hobbs, New Mexico

Drilling commenced 1/26 19 52 Drilling was completed 4/10/ 19 52

Name of drilling contractor Zephyr Drilling Corp. Address Hobbs, New Mexico

Elevation above sea level at top of casing 3580 feet. DF

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from none to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from none to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
13-3/8	72			284	Baker			
8-5/8	28			3984	Baker			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17-1/2	13-3/8	284	300	Circulated	Cement	
11	8-5/8	3984	1650	Circulated	Cement	

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHOULDER USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 9505 feet, and from feet to feet.

Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to producing Dry 19

The production of the first 24 hours was none barrels of fluid of which % was oil; %

emulsion: % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

Zephyr Drilling Corp.

Driller

J. A. Woody

Driller

Wm. H. Fort

Driller

Wm. O. Ingram

Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Midland, Texas

4/23/52

Place

Date

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	64	64	Surface
64	230	166	Red Bed & Rock
230	1000	770	Red Bed
1000	1615	615	Red Bed & Anhy
1615	2900	1285	Anhy & Salt
2900	3909	1009	Anhy & Gyp
3909	3925	16	Anhy & Gyp Lime
3925	4073	148	Lime
4073	4192	119	Lime & Anhy
4192	8811	4619	Lime
8811	8866	55	Lime & Chert
8866	8983	117	Lime
8983	9167	184	Lime & Shale
9167	9505	338	Lime