

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS REPORTS ON WELLS

FEB 17 PM 2:40

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	X	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	X

February 16, 1955

(Date)

Midland, Texas

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Wilshire Oil Company of Texas

(Company or Operator)

Carter

(Lease)

Brantly Drilling Company, Inc.

(Contractor)

Well No. 43-25 in the NE 1/4 SE 1/4 of Sec. 25

T. 20S, R. 38E, NMPM, D K Abo Pool, Lea County.

The Dates of this work were as follows: 1-29-55 thru 2-15-55

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on _____, 19____, (Cross out incorrect words)and approval of the proposed plan ~~was~~ (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

1-29-55 Perf. 5 1/2" 6940-7030. Swabbed down to 2 bbls. water/hr.
 1-31-55 Washed with 750 gal mud acid-swbd down. Treated w/ 2000 gal oil 1% AtPet, 263 gal propane, 200 gal gel, 2500 gal retarded acid. Swbd down to 5 bbls/wtr/hr.
 2-2-55 Plug @ 6975 w/ 8 gal hydramite-swbd 3 BP/hr 90% SW
 2-6-55 50 sx. cnt. plug w/ top @ 6733. Perf 6100 & squeezed w/ 50 sx. under plug @ 6085'.
 2-8-55 Perf. @ 6075 & 6030-tested for shut off o.k. Perf. 6040-6070
 2-9-55 Washed perfs w/ 500 gal mud acid-swbd dry. Treated w/ 3000 gal reg. acid and swbd dry
 2-10-55 20 sx. cement plug, top @ 6020. Perf. 4750-recemented casing w/ 100 sx.
 2-13-55 Perf 4530-4635 & 4655-4700- washed w/ 750 gal mud acid-swbd dry. Treated w/ 3000 gal acid. swbd dry down to 2 bbls San Andres water per hr.
 2-14-55 Spotted 35 sx plug 4721-4441. Shot off 5 1/2" casing @ 4324 & pulled. Spotted 10 sx. cement @ 4324 and @ 3070.
 2-15-55 Cut off 9 5/8" & pulled from 5414. Spotted 10 sx. plugs @ 540, 324 and at surface. D & A

Verbal approval to plug well obtained February 14, 1955.

Witnessed by A. T. Sindel, Jr. WILSHIRE OIL COMPANY OF TEXAS Div. Pet. Engr.
 (Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

M L Armstrong
(Name)

(Title)

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: A. B. Binsley

Position: Division Petroleum Engineer

Representing: Wilshire Oil Company of Texas

Address: 301 Leggett Bldg., Midland, Texas