

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Cruces

Lease No. 01170 (A)

Unit U. S. G. O.

SUNDRY NOTICES AND REPORTS ON WELLS

|   |                                     |   |
|---|-------------------------------------|---|
| NOTICE OF INTENTION TO DRILL.....                   | <input checked="" type="checkbox"/> | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        |
| NOTICE OF INTENTION TO CHANGE PLANS.....            | <input type="checkbox"/>            | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....     | <input type="checkbox"/>            | SUBSEQUENT REPORT OF ALTERING CASING.....       |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | <input type="checkbox"/>            | SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....  |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....        | <input type="checkbox"/>            | SUBSEQUENT REPORT OF ABANDONMENT.....           |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....    | <input type="checkbox"/>            | SUPPLEMENTARY WELL HISTORY.....                 |
| NOTICE OF INTENTION TO ABANDON WELL.....            | <input type="checkbox"/>            |   |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

SEAL-Burgor A-30 No. 2

Hobbs, New Mexico

August 31 1950

Well No. 2 is located 660 ft. from N line and 1930 ft. from E line of sec. 30

11/4 (Twp.) 20 (Range) 36 (Meridian)

San Jose (Field) San Jose (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is ..... ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well with rotary tools at the above location to a total depth of approximately 3690'. All casing points will be cemented in accordance with approved methods of the U.S. Geological Survey and any other special requirements will be complied with.

It is planned to use the following casing pattern: 9 5/8" casing to be set at approximately 250' and cemented with 250 sacks. Cement to be circulated to surface. 7" casing to be set at approximately 3700' and cemented with approximately 1200 sacks or sufficient cement to protect the salt section as determined by temperature survey.

Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Box 88

Hobbs, New Mexico

By [Signature]

Title District Superintendent

