

PROPOSED PLUG AND ABANDONMENT
3/3/00

Elev. = 3518' GL +13' KB

CIRCULATE 75 SXS CEMENT THRU PERFS AT 341' TO SURFACE

291' - 10 3/4" Casing. Cemented w/250 sxs. Circulated.

PERFORATE THE 5 1/2" CSG. AT 341'

MUD

SET A CEMENT RETAINER AT 1343'
SQUEEZE 30 SXS CEMENT THRU PERFS AT 1443'

1393' - 7 5/8" Casing. Cemented w/450sxs. Circulated.

PERFORATE THE 5 1/2" CSG. AT 1443'

SPOT 25 SXS CEMENT 2480'-2730'

T.O.C. @ 2428' (CBL)

C.I.B.P. @ 2730'

Perfs 2758'-2882'

C.I.B.P. @ 2930'

Perfs 2941'-3198'

Cement Plug 3111'-3116'

Sand 3116'-3250'

C.I.B.P. @ 3250'

Cement Plug 3560'-95'

C.I.B.P. @ 3595'

3625' - 5 1/2" , 17# Casing. Cemented w/425 sxs.

Cement 3770'-3789'

Sand 3789'-3864'

Fill 3864'-3900'

T.D. @ 3900'

CONOCO, INC.

S.E.M.U. #16

1980' FNL & 1980' FWL

Sec. 30, T-20S, R-38E

Lea County, NM