



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. LC 031695 (b)
Unit N.M.P.U.

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	☒	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Tarren Unit Mine No. 20 **Hobbs, New Mexico** **October 20**, 19**55**

Well No. **20** is located **1980** ft. from **[N]** line and **660** ft. from **[W]** line of sec. **34**

N 1/4 Section 34 **203** **38E** **N.M.P.U.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Tarry-Mine **Lee** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well at the above location to a total depth of approximately 8000' with rotary tools in an attempt to obtain commercial production in the Mine. All casing points will be cemented in accordance with approved methods of the U. S. Geological Survey and any other special requirements will be complied with.

It is planned to use the following casing patterns: 13 3/8" casing to be set at 225' and cemented with approximately 250 sacks cement to be circulated; 9 5/8" casing to be set at approximately 3000' and cemented with 1,563 sacks cement, or sufficient cement to protect the salt section as determined by survey; 7" casing to be set at total depth and cemented with 1,113 sacks cement, or as determined by survey, and to be perforated opposite the pay zone.

Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Continental Oil Company**

Address **Box 427**

Hobbs, New Mexico

By

Title **District Superintendent**

