

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other Instructions on
reverse side)Form approved.
Budget Bureau No. 42-R14245. LEASE DESIGNATION AND SERIAL
NEW Mexico 053460
Fed 1 C 15049

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Elliott Oil Company	8. FARM OR LEASE NAME Wylie
3. ADDRESS OF OPERATOR P.O. Box 1355 Roswell, N.M. 88201	9. WELL NO. 4-A
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' from north and 660' from west	10. FIELD AND POOL, OR WILDCAT Elliott Abo
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 9, T21S, R38E
15. ELEVATIONS (Show whether DE, RT, GR, etc.) 3583 DF	12. COUNTY OR PARISH Lea
	13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	(Other) ☐
(NOTE: Report results of multiple completion on Well Completion or Recapture Report and Log form.)			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The above described well has reached its economic limit and we propose to plug and abandon as follows:

1. Circulate the well bore with a gel mud.
2. 25 sk cement across perforations 7402-7552
3. 25 sk cement across top liner 4147
4. 35 sk cement across stub of 7" casing est 3100'
5. 35 sk cement plug at 1650'
6. 10 sk cement plug top of surface casing with marker installed.

- AMENDMENTS:
1. Place additional 25 sack cement plug at 5500-5800.
 2. Proposed 25 sack plug at liner top should be changed to a 35 sack plug in interval 3800-3950', or place additional plug in this interval.
 3. If 7" casing is not pulled, place 35 sack plug in interval 2800-2950'.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Owner

DATE

8/20/75

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

*See Instructions on Reverse Side

SEP 1 0 1975
JIM SIMS
DISTRICT ENGINEER