

Form C-101  
**DUPLICATE**

NEW 1 CO OIL CONSERVATION COMI ON  
Santa Fe, New Mexico

AUG - 1 1950

**RECEIVED**  
**HOBBS OFFICE**

**NOTICE OF INTENTION TO DRILL**

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Midland, Texas

July 21, 1950

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as Union  
Oil Company of California S. B. Fletcher "A" well No. 1 in SW/4 of NW/4  
Company or Operator Lease

of Sec. 5, T. 20-S, R. 39-E, N. M., P. M., So. Nadine Field, Lee County.

N

The well is 1930 feet (N.) (S.) of the North line and 330 feet (E.) (W.) of the West line of Section 5

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. - Assignment No. -

If patented land the owner is S. B. Fletcher

Address 956 A Street, Springfield, Oregon


If government land the permittee is -

Address -

The lessee is Union Oil Company of California

Address 200 Wilkinson-Foster Bldg., Midland, Texas

We propose to drill well with drilling equipment as follows: Rotary and Cable Tools



AREA 640 ACRES

LOCATE WELL CORRECTLY

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: Blanket Bond dated Sept. 11, 1947 with U.S. Fidelity & Guaranty Co.

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
11"	8-5/8"	28	New	325	Cemented	90
7-7/8"	5-1/2"	15.5	New	4350	Cemented	350

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 4350 feet.

Additional information: A temperature survey will be run on initial cement job of the oil string. If the well is commercial, the casing will be perforated at the top of original cement, then recemented with enough cement to tie into surface casing.

Approved AUG - 1 1950, 19\_\_\_\_  
except as follows:

Sincerely yours,

Union Oil Company of California  
Company or Operator

By James E. Rizo  
Position Assistant Petroleum Engineer

Send communications regarding well to:

Name A. P. Lookamp

Address 200 Wilkinson-Foster Bldg.  
Midland, Texas

OIL CONSERVATION COMMISSION,

By Ray Yorkmeyer  
Title OIL & GAS INSPECTOR

REC-12-14-88  
173