


## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## DUPLICATE MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<b>X</b>		

February 18, 1947

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Continental Oil CompanyState F-1-AWell No. 1

in the

Company or Operator

Lease

NE/4of Sec. 1T. 22-SR. 35-E

N. M. P. M.,

South Eunice

Field,

Lea

County.

The dates of this work were as follows: 1-29-47 - 2-10-47Notice of intention to do the work was (~~received~~) submitted on Form C-102 on January 27, 19 47and approval of the proposed plan was (~~received~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Cemented bottom of hole with 35 sacks cement from 3900' to 3650'. Filled hole with 12# mud from 3650' to 2700', set cement plug in 5 1/2" casing from 2700' to 2650'. Shot and parted 5 1/2" casing at 2600'. Set cement plug in 7 5/8" casing from 1800' to 1750'. Filled hole with 12# mud from 1750' to 750', set cement plug in 7 5/8" casing from 750' to 700'. Shot and parted 7 5/8" casing at 670'. Filled hole with 12# mud from 700' to point 50' below cellar inside 10 3/4" casing. Set bridge inside 10 3/4" casing at 50' and filled back with cement to bottom of cellar. Cellar filled and 4" marker set. Location restored to original condition.

Witnessed by \_\_\_\_\_ Name \_\_\_\_\_ Company \_\_\_\_\_ Title \_\_\_\_\_

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

18th day of February, 19 47Name X \_\_\_\_\_

Position \_\_\_\_\_

Dist. Supt.Representing Continental Oil Company  
Company or OperatorMy commission expires 5-17-49Address Box CC, Hobbs, New Mexico

Remarks

APPROVED

Date FEB 19 1947

Oil &amp; Gas Inspector

Name \_\_\_\_\_

Title \_\_\_\_\_