

NEW MEXICO OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

SUBMIT THIS NOTICE IN TRIPPLICATE TO THE DISTRICT OFFICE, OIL CONSERVATION COMMISSION, BEFORE THE WORK SPECIFIED IS TO BEGIN. A COPY WILL BE RETURNED TO THE SENDER ON WHICH WILL BE GIVEN THE APPROVAL, WITH ANY MODIFICATIONS CONSIDERED ADVISABLE, OR THE REJECTION BY THE COMMISSION OR AGENT, OF THE PLAN SUBMITTED. THE PLAN AS APPROVED SHOULD BE FOLLOWED, AND WORK SHOULD NOT BEGIN UNTIL APPROVAL IS OBTAINED. SEE ADDITIONAL INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION.

INDICATE NATURE OF NOTICE BY CHECKING BELOW

NOTICE OF INTENTION TO CHANGE PLANE		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO TEST DEEPER	
NOTICE OF INTENTION TO RIG NEW WELL	☒	NOTICE OF INTENTION TO RIG BACK		NOTICE OF INTENTION TO CEMENT	
NOTICE OF INTENTION TO CEMENT		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO CLOG (CHOK)	
NOTICE OF INTENTION TO REPERFORATE		NOTICE OF INTENTION TO (OTHER)		NOTICE OF INTENTION TO (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Robbs, New Mexico
(PLACE)

January 11, 1957
(DATE)

CONTENTS:

FOLLOWING IS A NOTICE OF INTENTION TO DO CERTAIN WORK AS DESCRIBED BELOW AT WELL

Humble Oil & Refining Company, New Mexico (State AR) WELL NO. 1, 1st
(OWNER OR OPERATOR)
NE 1/4, Sec. 14, T. 22-S, R. 35-E, N.M.P.M., DeBart
(LOCAL SUBDIVISION)
COUNTY.

FULL DETAILS OF PROPOSED PLAN OF WORK
(GIVE NOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

- Set cast iron bridge plug at 3725 feet and dump 10 feet of cement on top of plug.
- Well casing with a mud laden fluid.
- Place 10-60-60 cement plug in top of 5 1/2-inch casing.
- Place marker over well as required by NMOCC.

Casing program: 8-5/8-inch pipe set at 357 feet and cemented to surface.
5 1/2-inch pipe set at 3872 feet and cemented to 3941 feet.

Perforating interval: Perforated casing from 3755 to 3780 and 3831 to 3852 feet.
Open Hole from 3872 to 3941 feet (TD).

Latest Producing Test: 24 hours pumping, 7 barrels of load oil, 11 per cent water.
Approximately 850 barrels of load oil to be produced.

JAN 14 1957

APPROVED
BY: [Signature]
DISTRICT ENGINEER

Humble Oil & Refining Company
Agent
POSITION: Agent
THIS COMMISSIONED REPRESENTATIVE OF THE

APPROVED
BY: [Signature]
Engineer District 1

NAME: Humble Oil & Refining Company
ADDRESS: P.O. Box 1111, Santa Fe, N.M.