NEW MEXICO OIL CONSERVATION COMMISSION

Santa, Fe, New Mexico

MISCELLANEOUS NOTICES

HODES OFFICE

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below: NOTICE OF INTENTION TO TEST CASING NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL SHUT-OFF NOTICE OF INTENTION TO PULL OR NOTICE OF INTENTION TO CHANGE PLANS OTHERWISE ALTER CASING NOTICE OF INTENTION TO REPAIR WELL NOTICE OF INTENTION TO DEEPEN WELL NOTICE OF INTENTION TO PLUG WELL October 19. 1944 H obbs. N. M. Date OIL CONSERVATION COMMISSION, Santa Fe, New Mexico. Gentlemen: Following is a notice of intention to do certain work as described below at the State "U" Well No. 3 in CNW NE Skelly Oil Company
Company or Operator of Sec. 5, T. 22, R. 35, N. M. P. M., San SimonCounty. FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION Drilled to Total depth 4171' encountering sulphur water 4158' to 4165' which tested 1 bbl. per hour on 12 hour bailing test, and increase in water 4165' to 4171' which tested 32 bbls. sulphur water per hour on 12 hour bailing test. NO OIL OR GAS encountered to total depth. DRY HOLE Will plum and abandon as follows: Lead wool plug on bottom to plug off water then put in 15 sacks cement for cap, then fill hole with mud laden fluid to base of salt and run 15 sacks cement for plug. Will then fill hole thru salt section with mud laden fluid to top of slat where another 15 sacks cement will be run for a plug to protect salt section. Hole will then be filled with mud laden fluid to water points not behind pipe and cement plugs run, at each point to where 16" casing was cemented at 105'. After filling hole to surface with mud laden fluid will then install cement cap and pipe marker as set out in rules and regulations of the Oil Conservation Commission. 10 1944 19 SKELLY OIL COMPANY Approved -Company or Operator except as follows: Bv 01.32111 Dist. Supt. Position 0원 0년 - 호텔 Send communications regarding well to Name ... Skelly 041 0 ompa ny Address Hobbs N. M.

NEV TEXICO OIL CONSERVATION COM SSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

even though the work was witnessed by and sworn to before a notary public. S	y an agent of the (lee additional instru	Commission. Report ctions in the Rules	ts on minor operations n and Regulations of the C	eed not be signed Commission.
	ndicate nature of re			
REPORT ON BEGINNING DRILLING O	OPERA-	REPORT ON	REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEM- ICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING		
REPORT ON RESULT OF TEST OF C SHUT-OFF	ASING	REPORT ON	DEEPENING WELL	
REPORT ON RESULT OF PLUGGING	OF WELL			
-	Hobbs, N.	Place	Sept. 5, 194	A Date
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO. Gentlemen: Following is a report on the work done	e and the results of	otained under the h	eading noted above at th	e
Skelly Oil Company	State "	IJ#	Well No 3	in the
Company or Operator	e soo f	Lease	в 35	N M.P.M.
San Simon F				
The dates of this work were as follows:				
Drilled to 105' Redbed TD 105' with 100 sacks. job Sept. 1, 1944 @ 6:0 for water shut-off. 0.	- ran and or Let stand O P.M. then	mented 16" 48 hours at	fter completing	
Witnessed by Fred Whitaker	J. (C. Clower Company	Drill	ing Supt.
Subscribed and sworn before me this day of September	S, 19 44	I hereby swear of is true and correct Name Position Representing SI	Supt.	-
My commission expires Dec. 17	, 1944	Address Hobbi	, N. M.	
Remarks:			Roy 24	achrough

J

Title