

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL			
NOTICE OF INTENTION TO DEEPEN WELL		NOTICE OF INTENTION TO PLUG WELL	XX

HOBBS, NEW MEXICO

JANUARY 31, 1944

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

SKELLY OIL COMPANY

STATE "V"

Well No. 1

in CNE SE

Company or Operator

Lease

of Sec. 7, T. 22, R. 35, N. M. P. M., San Simon Field,

Lea

County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

Drilled to TD 4355' encountering water 4343' to 4355' testing 1 1/2 to 2 bbls per hour on bailing test. No oil or gas encountered below base of salt at 3950'. Will plug and abandon, driving lead wool plug to plug off bottom hole water. Will then fill hole with mud laden fluid to base of salt and run 15 sacks cement for plug. Will then fill hole with mud laden fluid to top of salt where another 15 sacks cement will be run for cap to protect salt section. Will fill hole with mud laden fluid to points where water encountered and not behind pipe and install cement plug at each water point to point where 16" casing was cemented at 110' with 70 sacks cement. After filling hole to surface with mud laden fluid will then install cement cap with pipe marker as set out in rules & regulations of the Oil Conservation Commission.

DRY HOLE - PLUG & ABANDON

JAN 31 1944

Approved _____, 19____
except as follows:

SKELLY OIL COMPANY

Company or Operator

By

Position

Dist Supt.

Send communications regarding well to

Name

SKELLY OIL COMPANY

Address

DRAWER "D"

HOBBS, N.M.

OIL CONSERVATION COMMISSION,

By

Title _____