

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

August 1, 1955
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Mexico "Z" Lease

Skelly Oil Company
(Company or Operator)

Well No. 1 in I
(Unit)

NE $\frac{1}{4}$ SE $\frac{1}{4}$ of Sec. 12, T. 22S, R. 35E, NMPM., Undesignated Pool
Lee County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

D rilled to total depth of 3921'. Set 8-5/8" OD casing at 335' and cemented to surface. Set 5 1/2" OD casing at 3921' and set with 200 sacks. Perforated 5 1/2" OD casing at 3894-3910'. No commercial production obtained. Set Baker C.I. bridging plug at 3850'. Squeezed perforations with 100 sacks cement at max. pressure of 6000#. Perforated 5 1/2" OD casing in intervals 3630-3830'. No commercial quantities encountered. Propose to plug to abandon in the following manner:

Will cut off 5 1/2" OD casing at approximately 2614' and pull same. Will fill with heavy mud-laden fluid to top of 5 1/2" OD casing then run 25-sack cement plug at top of 5 1/2" OD casing. Will fill with heavy mud-laden fluid to top of salt mf at 1781', then run 25-sack cement plug at 1781'. Will fill with heavy mud-laden fluid to surface, run 10-sack cement cap and install 4" pipe maker.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By J. G. Stanley
Engineer District
Title.....

Skelly Oil Company
Company or Operator

By [Signature]
Position Dist. Supt.
Send Communications regarding well to:

Name Skelly Oil Company
Address Box 38 Hobbs, New Mexico